

## Forestry (Mulching) Head

### ROTARY MOWER HEAD

A rotary mower provides a faster cut for brush and trees leaving a rougher cut than the flail's finer finish. Although the rotary requires additional safety precautions, it can cost you less to operate over the long haul.



### 36" FORESTRY HEAD

- Cuts up to 18" diameter (Mulching Head)
- Very fast production (up to 10x faster than a rotary head)
- Cuts with both the perimeter and bottom surface
- Ability to mulch material
- Highly efficient, hardened steel, replaceable teeth

### DIAMOND MOWER HEAD SPECS:

Mower Head	Head Weight	Features
50" Rotary	831 lbs	Cuts up to 8" material
60" Rotary	965 lbs	Cuts up to 8" material
22" Ditcher	600 lbs	Includes three 3/8" thick replaceable knives
42" Flail	639 lbs	Cuts up to 2" material
44" Flail	950 lbs	Cuts up to 6" material
50" Flail	1,068 lbs	Cuts up to 6" material
63" Flail	753 lbs	Cuts up to 2" material
48" Saw	775 lbs	Cuts up to 10" material
36" Forestry	780 lbs	Cuts up to 18" material





## MOWER HEADS

### Rotary Head



#### 50" AND 60" ROTARY HEADS

- Cuts up to 8" diameter brush and trees
- Diamond's exclusive Reinforcing Ring for longer life in heavy duty brush
- Proprietary Tri-Hex mulching disc provides greater inertia in tough conditions - and is covered by an unprecedented 5-year warranty

### Flail Head



#### 44", 50" AND 63" FLAIL HEADS

- 44" and 50" cuts up to 6" diameter grass/brush
- 63" cuts up to 2" diameter grass/brush
- Protective bonnet for safer operation
- Ideal when a finished cut is desired



# BuzzBar® Tree Limb Cutter (Saw Head)

## Power

The BuzzBar® is hydraulically-powered by a 38-HP hydraulic motor with power transferring from the motor to the blades by high performance Micro-V belts.

## Blades

The BuzzBar® features 26" diameter rotary saw blades made of 3/16" steel, capable of slicing through up to 6" diameter material. Each blade has 60 teeth that are set and filed. An extra set of blades is included with each unit.

## Spindles

Belt alignment problems are reduced due to precision machined spindle-housing surfaces. Grease pressure relief fittings are used to prevent blowout of shaft seals. Each shaft also has an anti-wrap guard to protect seals from debris. The AISI 4130 1-3/8" alloy steel spindles have tapered roller bearings for smooth operation and are factory pre-loaded.

## Durable

The cutting head main channel is one piece formed 3/16" thick steel coupled with 3/8" thick steel end plates for long life. The rear shield is made of 10-gauge steel and formed for stiffness making the cutter ideal for working in heavily vegetated areas.

## Easy Maintenance

The unit is easily maintained through a hinged belt guard with quick release fasteners for quick, easy access to the belt tensioner. The tension of the belt is adjusted with a simple slide mechanism. Grease fittings for each saw blade spindle are located on the front of the cutter for easy maintenance.

## Mounting

Mounts to all Alamo Industrial Boom Mowers including the Samurai™, Versa Boom, Machete™2, Rear Mount Boom, Xtreme® and the Maverick™, which are available in ranges from 17' up to 30'. When used in conjunction with the Quick Hitch™ quick attach system, the BuzzBar® can be taken off and switched with another head in minutes! (Some models of the BuzzBar® are not available for use with certain boom lengths – inquire with customer service for specific combinations.)



Quick Hitch™ quick attach system.

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products.

© 2009 Alamo Group Inc. Alamo Industrial and BuzzBar are registered trademarks of Alamo Group Inc.

**MEMBER OF THE ALAMO GROUP**  
ALWAYS ON THE CUTTING EDGE.

## Additional Specifications

Cutting Widths	48"	69"	90"
Approximate Weight	650 lbs.	705 lbs.	800 lbs.
Blades: 26" diameter, 3/16" steel. Extra set with each unit.			

Warranty: One year limited parts and labor. Non-governmental users are subject to modified policy. Only genuine Alamo Industrial parts should be used for warranty replacement.



**Always purchase genuine OEM parts.**  
1-800-356-6286

**ALAMO INDUSTRIAL**  
**BUILT SHARPER®**

1502 East Walnut St. • Seguin, Texas 78155

1-800-882-5762

www.alamo-industrial.com